



TECHNICAL DESCRIPTION S800-Vor2_TB_EN - 13.10.2017 - www.vs-furniture.com

Serie 800

Preliminary remark - carcass construction.

Series 800 element cabinets are supplied fully glued or disassembled, with eccentric connectors. The row of holes (dia. 3 mm) at a grid distance of 25 mm can be used right through.

Shelf carriers (load class L75) are screwed into standard-equipped cabinets [1] and screwed and inserted into individually equipped cabinets [2].

Adjustable shelf inserts [3] made from LIGNOpal (up to a width of 80 cm), coreboard (width 40 - 120 cm) and sheet steel (width 80 - 120 cm) have a concealed mounting for the shelf carriers.

Vertical carcass structures are fashioned by glued and, in the case of disassembled cabinets, by construction shelves [4] with eccentric connectors.

Horizontal carcass structures are fashioned by middle partitions flush with the carcass [5] or set back [6]. These are glued or, in the case of disassembled cabinets, equipped with eccentric connectors. Middle partitions flush with the carcass permit the use of separately closing single swing doors. Set-back partitions are combined with double swing doors.

Bases are a structural component of the carcass construction made from LIGNOpal [7] or are positioned as a steel base [8] at heights of 75 and 40 mm below the carcass. Both base types have precision height adjustment by means of an Allen key [9] through the bottom shelf. The LIGNOpal base can be fitted with a base cover strip flush with the front/door [10]. Base recesses [11] on the back are possible in the case of floor strips.

Wardrobe and washbasin cabinets are provided with plastic ventilation outlets on the top and bottom edges of the door. Erection: Models from a height of 197 cm or models with drawers and/or pullouts (DGUV Regel 108-007) must be secured to the wall or floor.

	Cupboard w	40	50	60	80	90	100	120	80	90	100	120	120	120
Profil 800	Shelf w	36,1	46,1	56,1	76,1	86,1	96,1	116,1	37,1	42,1	47,1	57,1	37,4	27,5
	Middle partition									1			2	3
*D=42,5	Load according to L75	10	13	15	21	24	27	32	10	11	13	14	10	7
*D=58	(kg)	14	18	22	30	34	38	46	11	16	18	22	14	