



PRODUCT INFORMATION LiteTable-ST\_TY\_US - 08.08.2018 - www.vs-furniture.com

## LiteTable-ST Stackable table.

Frame made from welded round tubular steel legs with all-round rectangular tubular steel top frame, all powdercoated. Because the inner and outer legs are arranged in pairs, the table is stackable (ST). What is more, they can be rotated to form continuous rows. The edge of the top frame is equipped with stacking and glide protection. Tables with glide elements for hard or soft floorings or with 2C universal glide elements and, optionally, with two castors at the outer legs.

Table sizes in 9 fixed heights in accordance with DIN EN 1729.

Table top Consisting of a CDF or LIGNOpal top and glued (KU) plastic border. Available with edged or rounded corners as required.

**Optionally i** t is also possible to use table connectors depending on the table arrangement (model 21003). **The following material groups are available to choose from:** Frame made of steel: M1; Top made of LIGNOpal: L4; Top made of CDF: L4.

Further products on this page: Compass-Soft.

|              |                |       |                                       |       |       | ₩·d fo | otprint |        |       |       |       |       |       |       |        | Ø     |  |  |  |  |
|--------------|----------------|-------|---------------------------------------|-------|-------|--------|---------|--------|-------|-------|-------|-------|-------|-------|--------|-------|--|--|--|--|
| LiteTable-ST | d = 275/8      | 21092 | 21093                                 | 21053 | 21054 | 21055  | 21056   | 21057  |       |       |       |       |       |       |        | 21002 |  |  |  |  |
|              | d = 311/2      |       |                                       |       |       |        |         |        | 21094 | 21095 | 21083 | 21084 | 21085 | 21086 | 21087  | 21003 |  |  |  |  |
|              | W              | 27%   | 551/8                                 | 63    | 707/8 | 783/4  | 86%     | 941/2  | 311/2 | 471/4 | 63    | 701/8 | 783/4 | 86%   | 941/2  |       |  |  |  |  |
|              | h              |       | 117/s:15¾·207/s·23¼·25¼·28·29½·30·32¾ |       |       |        |         |        |       |       |       |       |       |       |        |       |  |  |  |  |
|              | max. stack     | 8 4 8 |                                       |       |       |        |         |        |       | 4     |       |       |       |       |        |       |  |  |  |  |
|              | max. stack w*  | 381/4 | 653/4                                 | 687/8 | 763/4 | 84%    | 921/2   | 1003/8 | 421/8 | 571/8 | 68%   | 763/4 | 845%  | 921/2 | 1003/8 |       |  |  |  |  |
|              | max. stack d*  | 78    |                                       |       |       |        |         |        |       | 88    |       |       |       |       |        |       |  |  |  |  |
|              | Weight min. lb | 33,0  | 50,7                                  | 58,4  | 66,1  | 72,7   | 81,5    | 89,2   | 38,5  | 49,6  | 66,1  | 74,9  | 83,7  | 92,5  | 101,4  |       |  |  |  |  |